

TRHA 150

Two-Stage Liquid Ring Vacuum Pump



TRAVAINI

- PRESSURE RANGE** : 25 to 150 TORR
CAPACITY : 800 to 2200 CFM
- FEATURES** : Two stage rotating pump with externally located bearings grease lubricated
- SHAFT SEALING** : Mechanical seal - Double mechanical seal or stuffing box optional
- OPTIONS** : Bare shaft pump - Coupled to electric motor on baseplate - V-belt driven
- ACCESSORIES** : (Optional) Flange mounted air-liquid separator tank, non-return valve, vacuum relief valve, vacuum gauge and piped service liquid line with isolating valve, Y-strainer, 1/60/120 solenoid valve, flow regulating valve and compound gauge



TECHNICAL DATA

PUMP TYPE		TRHA 150-2000		TRHA 150-2600		TRHA 150-3100	
Speed	RPM	730	880	730	880	730	880
Motor - installed power	HP	100	125	125	150	125	200
Average service liquid flow	GPM	40	40	44	44	53	53
Noise level at 150 Torr	dB(A)	83	84	84	84	84	84
Minimum suction pressure	Torr	25	25	25	25	25	25

MODEL DESIGNATION

Standard Materials of Construction **					
Part No.	Description	F	RZ	RA	A3
106	Suction casing	Cast iron			Stainless steel AISI 316
107	Discharge casing				
137	Port plate				
110	Impeller housing	Carbon steel			
210	Shaft	Stainless steel AISI 420			
147	Manifold	Carbon steel			
357	Bearing housing	Cast iron			
230	Impeller	Ductile iron	Stainless steel AISI 316	Stainless steel AISI 316	

TRHA 150 - 3100 / C / GH	
T	Travaini manufacturer
R	Liquid ring pump
H	Two-stage pump
A	Design number
150	Flange size (mm)
3100	Nominal capacity (m³/h)
C	Shaft sealing C = Mechanical seal C2 = Double mech. seal B = Packing seal
F	Materials of construction-see table

**Special Materials Available Upon Request

- Request information on our HYDROSYS and DYNASEAL engineered vacuum systems
- For further information please consult Premier Fluid Systems Inc.



Premier Fluid Systems
 Canadian Home Of Travaini Pumps

Oct 2016
 Page 7.40