


DATA BASED ON :
 SUCTION DRY AIR 68 °F - 20 °C
 SUCTION PRESSURE 14.7 PSI
 SERVICE LIQUID WATER
 SERVICE LIQUID TEMPERATURE 59 °F - 15 °C
 TOLERANCE 10%

PERFORMANCE DATA
 TRAVAINI
 LOW PRESSURE
 LIQUID RING COMPRESSORS

PUMP MODEL	RPM	5 P.S.I.G.			10 P.S.I.G.			15 P.S.I.G.			20 P.S.I.G.		
		CAPACITY CFM	MOTOR HP	S.LIQUID G.P.M	CAPACITY CFM	MOTOR HP	S.LIQUID G.P.M	CAPACITY CFM	MOTOR HP	S.LIQUID G.P.M	CAPACITY CFM	MOTOR HP	S.LIQUID G.P.M
TRH 32-4	1750	2.3	0.5	0.9	2.7	0.7	0.9	2.6	0.8	0.9	2.4	1.0	0.9
TRH 32-20	3500	13	1.8	1.2	12.8	2.1	1.4	12	2.2	1.6	11	2.5	2
TRH 32-45	3500	28	3.0	1.2	28	3.8	1.4	27	4.3	1.6	24	5.0	2

****The above models can be used as compressors or vacuum pumps. Please see Page No. column to locate corresponding data sheets.
 For compressor performance curves refer to next page.**



Premier Fluid Systems
 Canadian Home of Travaini Pumps

4161 Morris Dr. - Unit 5 * Burlington * Ontario * L7L 5L5 * Website: www.pfspumps.com
 Tel: 1-800-461-2611 or 905-637-2611 * Fax: 905-333-4722 * email: info@pfspumps.com

DATE : APRIL 2012

Nº.: 11.1