


DATA BASED ON :
 SUCTION DRY AIR 68 °F - 20 °C
 SUCTION PRESSURE 14.7 PSI
 SERVICE LIQUID WATER
 SERVICE LIQUID TEMPERATURE 59 °F - 15 °C
 TOLERANCE 10%

PERFORMANCE DATA
TRAVAINI
 LOW PRESSURE
 LIQUID RING COMPRESSORS

PUMP MODEL	RPM	5 P.S.I.G.			10 P.S.I.G.			15 P.S.I.G.		
		CAPACITY CFM	MOTOR HP	S.LIQUID G.P.M	CAPACITY CFM	MOTOR HP	S.LIQUID G.P.M	CAPACITY CFM	MOTOR HP	S.LIQUID G.P.M
TRS 32-20	3500	13.5	1.2	0.8	13.3	1.5	1.7	10.2	2.4	2.5
TRS 32-50	3500	30	2.1	0.8	29	2.8	1.5	25	3.5	2.5
TRS 40-55	1750	38	2.2	1.5	29	3.3	3	15	4.6	4
TRS 40-100	1750	88	4.1	2.0	66	5.9	3	56	7.4	5

****The above models can be used as compressors or vacuum pumps. Please see Page No. column to locate corresponding data sheets.
 For compressor performance curves refer to next page.**



Premier Fluid Systems
 Canadian Home of Travaini Pumps

4161 Morris Dr. - Unit 5 * Burlington * Ontario * L7L 5L5 * Website: www.pfspumps.com
 Tel: 1-800-461-2611 or 905-637-2611 * Fax: 905-333-4722 * email: info@pfspumps.com

DATE : APRIL 2012

N°.: 11.1