


DATA BASED ON :
 SUCTION DRY AIR 68 °F - 20 °C
 SUCTION PRESSURE 14.7 PSI
 SERVICE LIQUID WATER
 SERVICE LIQUID TEMPERATURE 59 °F - 15 °C
 TOLERANCE 10%

PERFORMANCE DATA
TRAVAINI
 LOW PRESSURE
 LIQUID RING COMPRESSORS

PUMP MODEL	RPM	5 P.S.I.G.			10 P.S.I.G.			15 P.S.I.G.			20 P.S.I.G.		
		CAPACITY CFM	MOTOR HP	S.LIQUID G.P.M	CAPACITY CFM	MOTOR HP	S.LIQUID G.P.M	CAPACITY CFM	MOTOR HP	S.LIQUID G.P.M	CAPACITY CFM	MOTOR HP	S.LIQUID G.P.M
TRS 125-1250	880	550	30	13	535	40	22	-	-	-	-	-	-
	975	655	37	13	640	47	23	560	58	32	-	-	-
	1150	770	44	13	760	60	30	730	75	38	850	89	43
TRS 200-1950	735	1100	65	23	1180	88	37	1030	110	47	920	130	66
	880	1380	95	23	1380	126	37	1370	158	47	1240	185	66
	960	1570	115	23	1570	140	37	1530	170	47	1430	205	66
TRS 200-2500	735	1380	95	25	1360	120	38	1270	146	53	1130	183	67
	880	1770	139	25	1760	180	38	1890	195	53	1550	240	67
	960	1995	158	25	1985	195	38	1930	230	53	1810	270	67

****The above models can be used as compressors or vacuum pumps. Please see Page No. column to locate corresponding data sheets.
 For compressor performance curves refer to next page.**



Premier Fluid Systems
 Canadian Home of Travaini Pumps
 4161 Morris Dr. - Unit 5 * Burlington * Ontario * L7L 5L5 * Website: www.pfspumps.com
 Tel: 1-800-461-2611 or 905-637-2611 * Fax: 905-333-4722 * email: info@pfspumps.com

DATE : APRIL 2012

N°.: 11.1