

DATA BASED ON :
 SUCTION DRY AIR 68 °F - 20 °C
 SUCTION PRESSURE 14.7 PSI
 SERVICE LIQUID WATER
 SERVICE LIQUID TEMPERATURE 59 °F - 15 °C
 TOLERANCE 10%

PERFORMANCE DATA
 TRAVAINI
 LOW PRESSURE
 LIQUID RING COMPRESSORS

PUMP MODEL	RPM	5 P.S.I.G.			10 P.S.I.G.			15 P.S.I.G.			20 P.S.I.G.			25 P.S.I.G.			28 P.S.I.G.			35 P.S.I.G.			44 P.S.I.G.		
		CAPACITY CFM	MOTOR HP	S.LIQUID G.P.M	CAPACITY CFM	MOTOR HP	S.LIQUID G.P.M	CAPACITY CFM	MOTOR HP	S.LIQUID G.P.M	CAPACITY CFM	MOTOR HP	S.LIQUID G.P.M	CAPACITY CFM	MOTOR HP	S.LIQUID G.P.M	CAPACITY CFM	MOTOR HP	S.LIQUID G.P.M	CAPACITY CFM	MOTOR HP	S.LIQUID G.P.M	CAPACITY CFM	MOTOR HP	S.LIQUID G.P.M
TRVX 1003/W	1750	382	33	7	380	38	9	377	44	11	375	50	13	355	57	15	350	80	18	300	68	20	202	80	25
TRVX 1005/W	1750	482	38	7	475	44	9	455	50	11	446	55	13	405	62	15	890	65	17	335	73	22	250	84	28
TRVX 1007/W	1750	550	40	8	550	48	10	549	56	13	530	64	15	500	72	17.5	470	76	19	400	84	23	300	91	28

****The above models can be used as compressors or vacuum pumps. Please see Page No. column to locate corresponding data sheets.
 For compressor performance curves refer to next page.**



Premier Fluid Systems
 Canadian Home of Travaini Pumps

4161 Morris Dr. - Unit 5 * Burlington * Ontario * L7L 5L5 * Website: www.pfspumps.com
 Tel: 1-800-461-2611 or 905-637-2611 * Fax: 905-333-4722 * email: info@pfspumps.com

DATE : APRIL 2012

N°.: 11.1