TCD 32

Self-Cooling Centrifugal Pump for Heat Transfer & Vegetable Oils



travaini

HEAD : 10 to 475 FT.

CAPACITY : To 160 USGPM

FEATURES : No cooling required at all; Heavy-duty oil lubricated

bearings; No internal shaft sleeves; Easy back pull-out design for removal of the bearings & complete rotating element without removing the pump casing from the suction & discharge piping; Pump impeller balanced by means of back-ribs; Specially designed bearing housing attains low

operating temperatures in seal and bearing areas; **Note: "SP" design constructed for handling edible vegetable oils; For difference in GS and SP design

see respective sectional drawings.

SHAFT SEALING: Two seals in series: one mechanical seal for process

oil and one radial shaft seal for bearing lubrication oil.

OPTIONS : Bareshaft - Directly coupled to electric motor

mounted on baseplate

TEMPERATURE : To 608°F (320°C)

CASING PRESSURE : 232 PSI to 248°F (120°C); 150 PSI to 608°F (320°C)

VISCOSITY : To 1400 SSU

TECHNICAL DATA

PUMP TYPE		TCD 32-125		TCD 32-160		TCD 32-200		TCD 32-250	
Head, Max	FT	30	115	49	200	76	312	118	475
Capacity, Max	GPM	53	120	67	132	87	158	71	160
Speed	RPM	1750	3500	1750	3500	1750	3500	1750	3500
Max. Inlet Press.	PSIG	110	110	110	110	110	110	110	110

STANDARD MATERIALS OF CONSTRUCTION

PART No.	DESCRIPTION	GS	А3		
102	Volute Casing				
163	Casing Cover	Ductile Iron			
167	Cooling Plate		Stainless Steel AISI 316		
210	Shaft	Stainless Steel AISI 420			
230	Impeller	Cast Iron			
330	Bearing Housing	Cast from			
433.2	Mechanical Seal	Ni-Resist / Carbon / Viton	S.S. AISI 316 / Carbon / Viton		
502	Wear Ring	Carbon Steel	Stainless Steel AISI 316		

- For further information please consult Premier Fluid Systems Inc.

MODEL DESIGNATION

TCD 32 - 200 A / 2 - R / GS		
Т	Travaini Manufacturer	
С	Monostage Centrifugal Pump	
D	Heat Transfer Self-Cooling Centrifugal Pump	
32	Discharge Flange Size (mm)	
200	Nominal Impeller Diameter (mm)	
A	Hydraulic Design Status	
2 - R	Constructive Design Number - Single Mechanical Seal	
GS	Materials of Construction	

